

THÔNG SỐ CHI TIẾT CỦA CAMERA HK-2CE19D8T-PRO

Camera

Image Sensor:	2MP CMOS Image Sensor
Signal System:	PAL/NTSC
Effective Pixels:	1920(H)*1080(V)
Min. Illumination:	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens:	2.8mm, 3.6mm, 6mm optional
Lens Mount:	M12
Adjustment Range:	Pan: 0 – 360°, Tilt: 0 – 180°, Rotation: 0 – 360°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	1080p@25fps/1080p@30fps
HD Video Output:	1 Analog HD output
Synchronization:	Internal Synchronization
S/N Ratio:	More than 62 dB

General

Operating Conditions:	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±15%
Power Consumption:	Max. 4W
Weather Proof:	IP66
IR Range:	Up to 20m
Dimension:	Φ70×149.5 mm (Φ2.76’’ ×5.89’’)
Weight:	400 g